

TECHNICAL SPECIFICATION

Luda.Farm – SmartPlug – Art. No. 1071

GSM / Mobilnätverk

2G Dual-band 900/1800 MHz

Power Input / Puissance d'utilisation / Netzstrom / Ineffekt

AC110-250V/50Hz

Maximum Load / Puissance maximum / Maxim. Stromaufnahme

Maximal belastning

250V / 16A

Operating Temperature / Température de fonctionnement du capteur

Betriebstemperatur / Drifttemperatur

-20°C to +60°C

Storage Temperature / Température de stockage du capteur

Lagertemperatur / Förvaringstemperatur

-20°C to +70°C

Protection Class / Classe IP / Schutzklasse / Skyddsklass

IP20 only internal operation / IP20 utiliser à l'intérieur uniquement

IP20 nur Inneneinsatz / IP20 endast för inomhusbruk

Temperature Sensor Cable Length / Longueur du câble thermomètre

Temperatur Sensor Kabellänge / Längd kabel temperatursensor

3m

Temperature Sensor Range / Détection de la température

Temperatur Sensor Bandbreite / Räckvidd temperatursensor

-20°C to +70°C

Temperature sensor accuracy / Précision du thermomètre

Schwankungsbereich Temperatursensor / Noggrannhet temperatursensor

±2°C

SmartPlug

QUICK GUIDE



LUDA FARM

Luda.Farm, Krokslätts fabriker 30, 43137 Mölndal, Sweden



→ support.luda.farm

INCLUDED IN THE BOX



Luda.SmartPlug

Art. No. 1071



Temperature Sensor

Thermomètre
Temperatursensor

Art. No. 6052


INSTALLATION



My.Luda.Farm



PC/Mac



www.my.luda.farm



FUNCTIONS



Manual ON/OFF

Activation manuelle ON/OFF
Manuell Ein/Aus
Manuell Av/På-knapp

Reset

Réinitialiser
Zurücksetzen
Återställa

GSM

USB port - No function today

Port USB / Pas de fonctions aujourd'hui
USB Anschluss/ohne Funktion
USB-port - Ingen funktion i dagsläget



support.luda.farm